


NedZink titanium zinc with protective coating on the back

NedZink Pro-Tec



Product description

NedZink Pro-Tec is titanium zinc (EN 988) produced by NedZink with a protective coating on the back side for application on either cold or hot roof constructions. This protective coating protects the zinc against the effects of water vapour and other substances. The good processing properties of zinc are retained.

NedZink Pro-Tec can be used in all standard systems, but is mainly recommended for unventilated, damp proof hot roof and façade constructions.

NedZink Pro-Tec is available in various versions:



NATUREL Pro-Tec



NOVA Pro-Tec



NEO Pro-Tec



NOIR Pro-Tec



NUANCE Pro-Tec

In order to avoid fingerprints during application and assembly, the NedZink NOVA Pro-Tec, NedZink NEO Pro-Tec and NedZink NOIR Pro-Tec have an AFP-coating (Anti-Fingerprint) and the NedZink NUANCE Pro-Tec has a pigmented surface. These versions are supplied with a foil on the surface to protect the surface during transport and assembly.

The chemical composition, mechanical and physical properties and measurement tolerances of the base material are stipulated on the KOMO product certificate and the product certificate from Lloyd's Register, LRIQS (Approval QIS 122). The material properties are verified by an independent and neutral research institute on a random basis. The product certification and the ISO 9001 certificate for the quality management system at NedZink assure a constant and uniform high quality, meeting our own standards and far exceeding EN 988.

The Pro-Tec protective coating on the back suffices with regard to various quality requirements set in 'EN 13523' and 'EN 4628'.

Product range

Coils (NATUREL Pro-Tec, NOVA Pro-Tec, NEO Pro-Tec and NOIR Pro-Tec)

Width	600 mm – 1000 mm
Thickness	0,70 mm – 0,80 mm – 1,00 mm
Weight	max. 2800 kg (coils of 1000 mm)

Other sizes and thicknesses are on request.

NedZink NUANCE Pro-Tec is provided only on a project basis.


Cross-section and areas of application

Cross-section

- 1 NedZink standing seam system
- 2 Pro-Tec protective coating
- 3 Separating layer
- 4 Subconstruction

Areas of application

- 5 Gutters
- 6 Roofs and outer walls
- 7 Dormer side
- 8 Flat roofs



Transport and storage

NedZink products are packed and sent dry. The advice is to store titanium zinc dry and ventilated. This reduces the probability of condensation formation.

Processing

NedZink NOVA Pro-Tec, NedZink NEO Pro-Tec, NedZink NOIR Pro-Tec and NedZink NUANCE Pro-Tec are supplied with a foil on the surface to protect the surface during transport and assembly. This foil should be removed immediately and in one smooth motion after assembly at the construction site. Mechanical deformation of zinc below 7°C material temperature (and removal of the protective foil) is not allowed.

Properties of the material

A continuous stamp is applied to the back of all products in accordance with the provisions of EN 988 with the markings:

- NedZink NTZ
- The name titanium zinc in 4 languages; Dutch, German, French and English
- Product standard EN 988
- The nominal thickness
- Batch number
- Year of production
- Logos of KOMO and Lloyd's Register

The products supplied when incorporated within any system, compliant with the suppliers guidelines for processing and installation, will remain water impervious and not perforate due to manufacturing defects. For additional information about the product range and the processing of NedZink products, see our website www.nedzink.com



Netherlands

NedZink B.V.

Hoofdstraat 1
6024 AA Budel-Dorplein

Tel: +31 (0)495 455 700
E-mail: info@nedzink.com

Germany

NedZink GmbH

Im Lipperfeld 21
D-46047 Oberhausen

Tel: +49 (0)208 857 980
E-mail: info@nedzink.de

Belgium

NedZink N.V.

Avenue Jean-Etienne Lenoir 14
B-1348 Louvain-La-Neuve

Tel: +32 (0)10 452 727
E-mail: info@nedzink.be

France

NedZink SAS

1 Rue François Jacob
92500 Rueil Malmaison

Tel: +33 (0)7 68 60 95 37
E-mail: info@nedzink.fr

Watch our
corporate video:



www.nedzink.com

NedZink trademarks

NedZink® NATUREL, NedZink® NEO, NedZink® NOVA, NedZink® NOIR, NedZink® NUANCE,
NedZink® Pro-Tec, NedZink® STRUCTURE, NedZink® COMPOSITE and NTZ®.

Liability

This brochure was produced with the utmost care. All information specified in this brochure is according to our current knowledge, and gives information about our products and their uses. It is not, however, intended as a guarantee for certain properties of the products or their suitability for an actual application. One can therefore derive no rights from the content of this brochure.